



HLT SERIES

2 SPINDLES TAPPING MACHINE

HLT maintains all functions of HNT, the tapping range is also wider than HNT. It can be produced widespread products and suitable for the small quantity but various production requirements. Due to the adjustable speed function, which makes the machine operation to be easier and also maximizes the capacity.

HLT is suitable for tapping hexagon, square, flange and nylon nut. HLT has long tapping stroke design that can match the different length of tap while tapping the different kind of nut dimension or hardness.



Model	HLT-13	HLT-22	HLT-33	HLT-45	HLT-60	HLT-70	HLT-80
Tapping Size	M5~M10 No.10~3/8"	M10~M16 3/8"~5/8"	M16~M24 5/8"~1"	M24~M30 1"~1 1/4"	M30~M39 1 1/4"~1 1/2"	M36~M45 1 3/8"~1 3/4"	M42~M52 1 3/4"~2"
Max. A/C (mm)	23	35	46	55	69	81	98
Max. Capacity (Pcs/Min)	180	100	50	20	15	10	4
Main Power(KW)	1.5	2.2	5.5	2.2(1:5S)	3.7 (1:5S)	3.7 (1:5S)	5.5 (1:15S)
Max. Power Consumption(KW/h)	3.7	6.3	9.3	7.1	10.8	10.8	14.4
Pneumatic Consumption (L/Min)	128	252	247	282	217	145	120
Oil Tank(L)	170	300	400	550	600	650	800
Machine Dimension (W×L×H/m)	1.10x1.30x1.70(B) 1.60x1.40x1.70(C)	1.40x1.70x1.90(B) 2.00x2.40x1.90(C)	1.50x1.90x2.10(B) 2.10x2.60x2.10(C)	1.80x2.00x2.30(B) 2.30x2.80x2.30(C)	2.00x2.10x2.50(B) 2.40x2.80x2.50(C)	2.00x2.10x2.50(B) 2.60x2.80x2.50(C)	2.60x3.00x2.70(B) 2.70x3.10x2.70(C)
Net Weight(Kg)	985(B) 1280(C)	1500(B) 1960(C)	2000(B) 2710(C)	2800(B) 3450(C)	4000(B) 4500(C)	4300(B) 4700(C)	5200(B) 5400(C)